



Devermini Municipality Office of the Municipal Executive Pragatinagar, Nawalparasi East Gandaki Province, Nepal

Invitation for Catalogue Shopping of Tractor, Silage balor and Accessories

(date of publication 2079/11/18)

Devchuli Municipality, Nawalparasi East intends to procure a tractor, silage balor and accessories as listed on the table below, under the Catalogue Shopping Procedure as described on the Public Procurement Act, 2063. All eligible manufacturers or authorized dealers are invited to submit proposal with their catalogue containing technical data, aurorized specifications, quality, price including facilities . Proposal must submit within 7 (Seven) days of publication date during office hour at Office of the Municipal Executive of Devchuli Municipality. The manufacturers or authorized dealers must submit copies of firm registration certificate, business registration certificate, VAT and PAN registration certificate, tax clearance certificate until F/Y 2078/79, self declaration letter and the letter of manufacturer's authorization along with the application. If the last day fals public holiday, it is possible to be submit next day.

S.N.	General Specifications	Unit	Quantity	Remark
5.IN.	Supply and delivery of tractor with trolley	Pcs	1	
2	Supply, delivery and instalation of silage balor and accessories			As per approved
2.1	Silage balor	Pcs	1	technical
2.2	Accessories			specifications.
2.2.1	Mobile shredder	Pcs	1	-
2.2.2	Static shredder	Pcs	1	
2.2.3	Hydraulic trolley	Pcs	1	

For any query and detailed specifications, please visit official website of Devchuli municipality <u>https://www.devchulimun.gov.np</u> or contact 9855053602.

lel C मोहन प्रसाद मरासिर्न দৰ্বৰ দেগমেকাৰ সায়িক্ৰ



<u>Technical Specification for Procurement of Tractor, Implements, Silage balor and</u> <u>accessories</u>.

Mobile Shredder CRITERIA	REQUIREMENT	OFFERED SPECIFICATION
Number of Rows	1	
Length (mm)	2700 ±50mm.	
Height with exhaust	2800 ±50mm.	
(mm) Width (mm)	Not less than 1800 00 mm	
Weight (Kg)	660 ±50 kg.	
Tyres	Metal Wheel 16X6.5	
3 Point hitch	Cat-II	
PTO RPM	540	
	≥45 HP	
Minimum Suitable power of Tractor(HP)		
Exhaust Direction	360 degree Adjusted Manually	
Chopping Knives	≥12	
	Minimum 2	
Cutting Knives	5 ± 3	
Chopping Length	5 ± 5	
(mm)	Not less than 5 Tonne / Hour	λ
Capacity	All signs and instructions in the vehicle	
Instructions	shall be in English.	
Manuals	One copy of the Operator's and Owner's	
Manuais	Instructions in English shall be supplied	
	with each vehicle.	
Tools	A set of tools required for general	
10015	maintenance shall be supplied.	
Proven performance	The hidder shall provide the	
r loven periormanee	manufacturer's data of the performance	
	of the unit to include the fuel	
	consumption and performance curve of	
	the engine.	
Warranty	The manufacturer shall provide a	
	minimum of one-year warranty after	
	acceptance.	
Initial Service	The supplier shall provide the	
	machinery with all the necessary filters	
	and spare parts required for the first one service, after the machineries has been	
	service, after the machineries has been	
	accepted.	
Offered price :		allott
		TIESON IFEINE OFEINEN
		difeon newson
		hole



Static Shredde CRITERIA	REQUIR	EMENT			OFFERED SPECIFICATION
tem Name	Metal	Thickness	Otv.	Dimension	,
term r turne	Туре	(mm)		L x W x H (mm)	
Static shredder	1990	()		1930*1473*4191 (±50) mm.	
Hopper	M.S.	2 - 5	1	975 x 661 x 465 (±50) mm.	
юррег	plate		1		
Heavy Duty	4	8	1	Dia. (620 x 128) ±10mm.	· · · · · · · · · · · · · · · · · · ·
Fly Wheel	500/7	°	-		
Blades	Tungsten	7	6/	270 x 88 x 25(±10mm.)	
	Coated		12		
	Boron				
	Steel				
Blade	M.S.	5 & 17	1	Dia. (285 x 29)	
Sharpening	plate &				
Device	A-60				
Fabrication for	Mild	4mm	1	1828*760*1422*660(±50	
Motor Mount	steel			mm.)	
Material,					· · · · · · · · · · · · · · · · · · ·
Gauge and				· · · · · · · · · · · · · · · · · · ·	
Dimension)					
Chute Size	M.S.	2 to 8	1	590 x 465 x 468(±25 mm.)	
	plate				
Shredder				Maximum 600±25 Kg	
Weight					
Gross Unit			3. (Cer	Maximum 780 ±25Kg	
Weight					
(Shredder	ł				
Fabricated	, 1 m		1.55		
Frame -					
Motor)		1. T. 1. 23			
Per Hour				Minimum 4.5 Tonne / Hr	
Chopping				Depends on material	
Capacity					
Motor-15				3 phase power connectivity	
HP,1400 RPM			<u> </u>		
		and instru	ction	s in the vehicle shall be in	
Instructions	English.				
Manuals	One copy	of the Op	berato	r's and Owner's Instructions ir	
	English shall be supplied with each vehicle.				
Tools	A set of tools required for general maintenance shall be				e
	supplied.				
Proven	The bidd	er shall pr	ovide	the manufacturer's data of the	

्रिटिन प्रसाद मरासिनी मनस्य प्रयासकाय आहालस्य प्रमुख प्रयासकाय आहालस्य



performance	performance of the unit to include the fuel consumption	
	and performance curve of the engine.	
Warranty	The manufacturer shall provide a minimum of one-year	
	warranty after acceptance.	and the second
Initial Service	The supplier shall provide the vehicle with all the	ж
	necessary filters and spare parts required for the first	
	one service, after the machinery has been accepted.	
Offered price :		

3. Silage baler

CRITERIA	REQUIREMENT	OFFERED SPECIFICATION
Kerb Weight	1450±100 kg.	
Capacity of Hopper	200 kg±10 kg.	
Size of chamber (L x H)	500 mm x 500 mm (±20 mm.)	
Chamber width	500 mm (±20 mm.)	· · · · · · · · · · · · · · · · · · ·
Conveyor size	3000 mm x 500 mm with chain on both sides (6000 mm)	
Conveyor stand dimension	640 mm x 470 mm x 720 mm(±20mm.)	
Conveyor side plates	2775 mm x 225 mm (±50 mm)	
Internal film shaft length	550 mm ±25 mm.	
External film shaft length	370 mm±25	
Operation System	Hydraulic	
Power Source	3-Phase 5 HP- electric motor	
Hydraulic Tank Capacity	Not less than 120 L	
Machine Output (bales/hr)	18-32 bales per hour	
Machine Output (in MT) *	Not less than 20 MT per day	
Bale Dimensions	490 x 490 ±20 mm.	
Bale Weight	50–90 kg (Depends upon the moisture of raw material)	
Compaction Density	$625 \pm 50 \text{ kg/m}^3$	
Ground clearance	Not less than 190 mm	
Offered price :		\cap

O LON TEON FRING STELETON USES FERRED A STELES



4. Tractor

2.44

CRITERIA	मण्डकी घ्रदेश, क्रेयाल REQUIREMENT	OFFERED
		SPECIFICATION
General	Farm Tractor, Four Wheel drive, suitable for farm	
	work driving giving smooth economic performance	
	and in suitable for hilly area in Nepal Ground	· · · ·
	Clearance should be minimum 400 mm. Total	
Engina	weight of vehicle shall not be less than 2000 kgs.	
Engine	4-Stroke, min 3 cylinders water cooled Diesel	
	Engine, developing Maximum rated power output not less than 55 HP category at rated rpm,	
	Rotary type fuel injection pump will be highly	
	preferred.	
Gauges	To include speedometer, water temperature, as	
	necessary for efficient operation and maintenance.	
Clutch	Dual clutch (diaphragm Clutch / Dry type) or	
	suitable for Transmission.	
Transmission	Manual shift at least eight forward and two reverse	
	gears (Constant mesh / Synchromesh gear mesh	
Charada and E	type)	
	Steel heavy Duty with toe-hooks.	
Hydraulic Lifting	Not less than 1400 kgf	
capacity Fuel tank	More than 60 litres.	
Air cleaner	Oil Bathed /Dry type	
Cooling System	Water cooling	
Weight	More than 2000 Kg	
Wheelbase	Minimum 2000 Kg	
Fires		
	Standard size suitable for operation in hilly area too.	
Hitching system	3 Point hitching system	
Steering	Power Steering	
Brakes	Suspended type / Oil immersed brake	
Essential Accessories	1. Head light, reversing light and turn signals	
	2. Speedometer / odometer, Standard tool set with	
	jack and handle.	
	2 Equipped with all second control $(0, 1)$ is the 1-1	
	3 Equipped with all accessories offered in standard model but not limited to the above items. The	•
	accessories / features supplied with the tractor shall	
	be as per manufacturer's standard.	
nstructions	All signs and instructions in the vehicle shall be in English.	0
		THE ANTINIA
	महि	NEW EROSEN
	U	La no.



Manuals	One copy of the Operator's and Owner's Instructions in English shall be supplied with each vehicle.	
Tools	A set of tools as required for general maintenance shall be supplied.	
Color	Standard colour	
Proven performance	The bidder shall provide the manufacturer's data of the performance of the unit to include the fuel consumption, performance curve of the engine.	
Warranty	Manufacturer shall provide a minimum of Two-year warranty after acceptance.	
Initial Service	The supplier shall provide the vehicle all the necessary filters and spare parts required for the first two services, after the vehicle has been accepted.	
Offered price :		

5 Hudraulic trailor

CRITERIA	REQUIREMENT	OFFERED SPECIFICATION
General	Hydraulic trailer of minimum size (L*B*H)10*6*2.5 feet with 1.5 feet extension of height with rear tire size 9.00-16.00 to be provided	
Chassis	Chassis specification to be made from 150*75 MS channel section.	
Trailer material	Trailer floor should be made from 4 mm MS plate and Trailor side plates should be made from 3.55 mm MS plate with 50mm*50mm*8mm angle frame.	
Axle	Axle size should be 90*90 mm square and steel hub should be provided.	
lift	Should have proper hydraulic boom to lift to minimum 20 ton.	
Other	Enamel paint double coat of standard colour should be done after initial red oxide priming all over trailor.	
Offered price :		

Note :

- The supplier must be delivered all item to Devchuli Municipality, ward number 16, Rajhar Nawalpur .
- The supplier must be installed/fitting machinery parts as office required.
- The supplier authorized person must be signed and stamp each page of specification.

...catic Vey alleon Irenta arenteral Insta Irentalia antioner